

Una Tempo Stripe Broadloom

Product Description



Product description	Methods	Product data
Construction		
Structure	ISO 2424	Tufted loop pile
Gauge	ISO 2424	1/10
Pile material	DIR 96/73, 96/74	100% Solution dyed Polyamide
Coloration	-	Solution dyed
Backing	eTL	WT - Woven textile
Dimensions	ISO 3018	Approx. 400 cm
Total thickness	eTL	Ca. 5,5 mm.
Surface pile thickness	eTL	Ca. 2,5 mm.
Total carpet weight	ISO 8543	Ca. 2.200 g/m2
Pile yarn weight	eTL	500 g/m2
	.	14.75 oz./yd2
edge soil protection	eTL	Yes

Performance ratings

Performance areas	EN 1307	Class 33 Commercial - Heavy
Castor chair suitability	eTL	Yes, constant use
Suitable for use on stairs	eTL	Yes
Static control	eTL	Permanently antistatic
Suitable for underfloorheating	ISO 8302	Yes

Safety & Environment

Fire classification	D,DIBT AbZ.no.	Z-156.601-441
	EN 13501-1 Euro Class	Bfl-s1
CE Labeling	EN 14041	Certified
	CPR	1020-CPR-006-1/16
	Declaration of Performance	DOP 1B-PA-WT
	Notified body no.	1021
	Ce Year	12
	Slip resistance EN 13893	Class DS
Indoor air	DIM Certifikat	No.006
	M1	With WTA Backing
	Green Label Plus	Approved
	Environmental Choice NZ	Approved

Guides

Installation+adhensive guide	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais
Cleaning, stain removal	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais

Manufacturer

Product description	Methods	Product data
Factory certification	ISO 9001	Audited and verified by BVC
	ISO 14001	Audited and verified by BVC
	EMAS	Audited and verified by BVC
	OHSAS	Audited and verified by BVC
	DS 49001	Audited and verified by BVC
	CRuk	Member of Carpet Recycling UK
	TransQ	Qualified