

Epoca Moss

Product Description

 Antismudsbehandlet
Antisoiling protected
Schmutzabweisend
Traitée antisalissure

  contract
CERTIFICATE

  Cfl-s1



ege

THE URGE TO EXPLORE SPACE

Product description	Methods	Product data
Construction characteristics		
Structure	ISO 2424	Tufted cut pile
Gauge	ISO 2424	1/8
Pile material	DIR 96/73, 96/74	100% polyamide
Coloration	-	Continuous dyed
Backing	eTL	WT - Woven textile
Dimensions	ISO 3018	Approx. 400 cm
Total thickness	ISO 1765	Apr 11,5 mm.
Surface pile thickness	ISO 1766	Apr 9,0 mm.
Tufts	ISO 1763	Apr 140.900 pr.m2
Total carpet weight	ISO 8543	Apr 2.925 g/m2
Pile yarn weight	eTL	1.750 g/m2
Surface pile density	ISO 8543.	Apr 0,150 g/cm3
Soil protection	eTL	Yes
Performance characteristics		
Performance areas	EN 1307	Class 31 Commercial - Moderate
Guarantee	eTL	Contract certificate
Static control	eTL	Permanently antistatic
Light reflectance	eTL	Testreport
Colour fastness to light	ISO 105-B02	>5
Colour fastness to rubbing wet	ISO 105-X12	>3
Colour fastness to rubbing dry	ISO 105-X12	>3-4
Colourfast. to water patterned	ISO 105-E01	>4
Safety & Environment		
Fire classification	EN 13501-1 Euroclass	Cfl-s1
Indoor climate	DIM certificate	No. 006
Guides		
Installation + adhesive guide	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais
Cleaning, stain removal	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais
Manufacturer characteristics		
Factory certification	ISO 9001	Audited and verified by BVC
	ISO 14001	Audited and verified by BVC
	EMAS	Audited and verified by BVC
	DS/OHSAS	Audited and verified by BVC
	DS 49001	Audited and verified by BVC
	CRuk	Member of Carpet Recycling UK

Product description	Methods	Product data
	TransQ	Qualified



THE URGE TO EXPLORE SPACE