

# Una Micro Stripe Ecotrust

## Product Description



Product description	Methods	Product data
<b>Construction</b>		
Structure	ISO 2424	Woven loop pile
Pile material	DIR 96/73, 96/74	100% Polyamide
Coloration	-	Solution dyed
Backing	eTL	Ecotrust 350, 100% recycled
Dimensions	ISO 3018	48x48/96x96 cm
Total thickness	ISO 1765	Ca. 5,0 mm.
	.	0.20"
Total carpet weight	ISO 8543	Ca. 2.400 g/m2
	.	70.8 oz./yd2
Pile yarn weight	eTL	480 g/m2
	.	14.16 oz./yd2
edge soil protection	eTL	Yes

### Performance ratings

Performance areas	EN15114	Class 33 Commercial - Heavy
Wear guarantee	eTL	Contract certificate
Castor chair suitability	eTL	Yes, constant use
Suitable for use on stairs	eTL	Yes
Static control	eTL	Permanently antistatic
Acou.insu. from impact noise	eTL	16 dB
Acoustical absorption	eTL	0,20 aW
Suitable for underfloorheating	ISO 8302	Yes
Colour fastness to Light	ISO 105-B02	>5
	AATCC 16	5.0
Colour fastness to rubbing wet	EN ISO 105-X12	>3
	AATCC 165	5.0
Colour fastness to Rubbing Dry	EN ISO 105-X12	>3-4
	AATCC 165	5.0
Colourfast. to Water Patterned	EN ISO 105-E01	>4
Cleaning	AATCC 138	5.0
Colour fastness to Ozone	AATCC 129	5.0
Colour fast.Oxides of Nitrogen	AATCC 164	5.0
Other performance tests	ASTM D5252 Hexapod	5.0/ 5.0
	-	Commercial - Heavy
	AATCC 134 Electrostatic propensity	0.8 kV

### Safety & Environment

Fire classification	DK,MK GODKENDELSE	Godkendt
	D,DIBT AbZ.no.	Z-156.601-675
	ASTM E-648	Class 1
	ASTM E662 Smoke Density	<450
	ASTM D2859 Surface Flamm.	Pass
	EN 13501-1 Euro Class	Cfl-s1
CE Labeling	EN 14041	Certified
	CPR	1021-CPR-010-2/16
	Declaration of Performance	DOP 5C-PA-ECT350
	Notified body no.	1021

Product description	Methods	Product data
Indoor air	Ce Year	14
	Slip resistance EN 13893	Class DS
	DIM Certifikat	No.006
	Green Label Plus	Approved
	Emissions dans l'air intérieur	A+/A+
Environment	GECA	Approved
	BREEAM-NOR	With EcotrustA Backing
	Environmental Product Decl.	EPD-EGE-20140127-CBC1-EN
	Cradle To Cradle	Ecotrust,C2C Certified
	Recycled Content, ISO 14021	Ca. 15,0 %
	Recycled Content for LEED	Ca. 15,0 %
	LEED	Qualified

### Guides

Installation+adhensive guide	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais
Cleaning, stain removal	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais

### Manufacturer

Factory certification	ISO 9001	Audited and verified by BVC
	ISO 14001	Audited and verified by BVC
	EMAS	Audited and verified by BVC
	OHSAS	Audited and verified by BVC
	DS 49001	Audited and verified by BVC
	CRuk	Member of Carpet Recycling UK
	TransQ	Qualified